

[54] **CATHETER FOR REPAIR OF BLOOD VESSEL**

[75] Inventors: Kyuta Sagae, Fuji; Naoto Takemura, Fujinomiya; Yoshiaki Sugiyama, Numazu; Susumu Tanabe, Fujinomiya, all of Japan

[73] Assignee: Terumo Kabushiki Kaisha, Tokyo, Japan

[21] Appl. No.: 35,444

[22] Filed: Apr. 7, 1987

[30] **Foreign Application Priority Data**

Apr. 9, 1986 [JP] Japan 61-80089

[51] Int. Cl.⁴ A61M 29/02

[52] U.S. Cl. 604/53; 604/101; 128/344; 128/325

[58] Field of Search 604/96-103, 604/53; 128/344, 348.1, 325

[56] **References Cited**

U.S. PATENT DOCUMENTS

4,423,725 1/1984 Baran et al. 604/101
4,573,966 3/1986 Weikl et al. 604/101
4,636,195 1/1987 Wolinsky 604/53

4,641,653 2/1987 Rockey 609/96
4,655,246 4/1987 Daniels et al. 604/53

FOREIGN PATENT DOCUMENTS

0654214 2/1986 Switzerland 604/101

Primary Examiner—Dalton L. Truluck

Assistant Examiner—Frank Wilkens

Attorney, Agent, or Firm—Frishauf, Holtz, Goodman & Woodward

[57] **ABSTRACT**

A catheter for the repair of an injured blood vessel, characterized by comprising a multiple-lumen type catheter tube having at least two tubular cavities, at least one dilating member disposed in the distal portion of said catheter tube and adapted to communicate with one of said tubular cavities, a lateral hole for the injection of a blood coagulation accelerant disposed on said catheter tube at the proximal side than said dilating member side and adapted to communicate with the other tubular cavity, and a hub having a plurality of flow conduit communicating severally with said tubular cavities of said catheter tube and adapted to communicate with the proximal portion of said catheter tube.

7 Claims, 4 Drawing Sheets

